

*ISO 9001:2015 & ISO 14001:2015
ISO 14064:2018 & ISO 14067:2018
ISO 27001:2022 & ISO 50001:2018
CERTIFIED MANUFACTURER*

UPDATE SEDEX, BSCI, WCA, FSC, REACH & RoHS



**New
Products**

2024

A GLOBALLY ORIENTED MANUFACTURER OF SELF-ADHESIVE TAPE


Recycled OPP Tape No.RPP



Feature/Usage

- Sustainable packaging tapes to enable a circular economy.
- Suitable for sealing boxes and bundling goods at home, school, office, factory, warehousing and logistics company, etc.

Recycled PE Cloth Tape No. ROCH35



Feature/Usage

- Sustainable packaging tapes to enable a circular economy.
- Strong adhesion and high tensile strength.
- Widely used for heavy-duty packaging, carpet jointing, book mounting protection.

Recycled PET Double Sided Tape No.RDST



Feature/Usage

- Sustainable double-sided stick tapes to enable a circular economy.
- Adhere posters, photos, public notes, envelopes.
- Fixing of ornament, hook or sign board.
- For laminating nameplate.
- Shoe & leather industry.
- For computerized embroidery.

Recycled PET Packaging Tape No.RPET



Feature/Usage

- A strong and abrasion resistant backing.
- PET film guarantees an excellent printability with all types of ink systems. Can be disposed together with the box into the blue bin.
- Good performance on recycled cardboard.
- Suitable for manual and automatic dispensers.


Recycled Weather Proofing Tape No.RWPT



Feature/Usage

- Made from 100% recycled PE plastic.
- Excellent resistance to aging and degradation, making it a reliable choice for long-term weather sealing.

Recycled Tapes Made From Recycled Plastic



Performance

Items	RPP	ROCH35	RDST	RPET	RWPT
Backing	Recycled OPP Film	Recycled PE Film +Cloth(35mesh)	Recycled PET Film		Recycled PE Film
Adhesive	Acrylic Emulsion	Hot Melt	Acrylic Emulsion		
Colors	Yellowish, Clear	Silver	Clear		
Adhesion To Steel (N/in)	≥6	≥14	A Side: ≥3.43 B Side: ≥2.45	≥7.84	9.6
Tensile Strength (N/in)	≥77	≥83	≥90	≥90	45
Elongation (%)	≥120	≥25	≥100	≥100	300
Total Thickness (mm)	0.048±0.002	0.175±10%	0.087±0.005	0.050±10%	0.105-0.165



Compostable Tape

No.CPT, PCPT



Feature/Usage

- Compostable tape is made by Cellulose film and natural latex, and it is biodegradable and compostable.
- No pollution and no bad impact on the environment.

Parcel Paper Tape No.KHT



Feature/Usage

- Eco paper parcel tape with zero plastic.
- Can be left on the cardboard carton when it is recycled, save a lot of labour.

Rubber Kraft Paper Tape

No.SK-04



Feature/Usage

- Made with 100% kraft paper.
- Non-PE-Coated! No-Chemical -Ink! Convenient to recycle with box without separation.
- The degradation effect reached 62.528% after 64 days.
- Ideal for labling boxes, cleaning writing surface. Simply tear, but high tensile strength. Compatible with regular tape dispensers.

Removable Box Kraft Paper Tape No.SK-05



Feature/Usage

- No scissors or dispenser needed! Easy to tear. No harm to the box when it was peeled off so you can reuse boxes again and again.

Rubber Bopp Packaging Tape

No.OPR



Feature/Usage

- Used for packing and sealing, etc. Strong anti-fog ability. Strong adhesion. Widely used for manual or automated sealing, bundling, wrapping.

Rubber Masking Tape

No.SMR-02



Feature/Usage

- Rubber adhesive, strong adhesion, soft and fit. No adhesive residue. Easy to tear. Can be written on. Widely used in indoor and outdoor painting masking, car painting, furniture protection, etc. Heat resistance 120 °C.

Performance

Items	CPT/PCPT	KHT	SK-04	SK-05	OPR	SMR-02
Backing	Cellulose Film		Kraft Paper		BOPP	Crepe Paper
Adhesive	Natural Latex	Hot Melt	Natural Latex	Hot Melt	Natural Latex	
Colors	Clear (CPT) Customized Design (PCPT)	Mid Brown	Brown		Clear	Natural Color
Adhesion To Steel (N/in)	≥ 4.0	≥ 15	≥ 9.8		≥ 5.0	≥ 9.8
Tensile Strength (N/in)	≥ 70	≥ 100	≥ 100		≥ 100	≥ 79
Elongation (%)	20-150	≥ 5	N/A		≥ 150	N/A
Total Thickness (mm)	0.040-0.060	0.130±0.005	0.130±10%	0.110±10%	0.040-0.060	0.140±10%



Aluminum Film Pearl Cotton Tape No.APCT



Feature/Usage

- Shockproof, waterproof, dustproof, sunscreen, heat preservation and heat insulation.
- Suitable for building ice bags, handbags, bags, sun shades, car cushions, etc.

Window Insulation Tape No.WIT



Feature/Usage

- Blocking drafts and air leaks that lead to high heating costs in winter. Applying to the inside of your window to seal out the cold from getting into your home. Good visibility and easy & quick installation and removal. Making your home more comfortable and energy efficient all year long.

Double Sided Fibreglass Tape No.DSFT



Feature/Usage

- Fiberglass as backing, strong and tough!
- Wide applications: such as soundproofing, air-tight sealing, window and door frames sealing, packaging, logistics, etc.

Non-slip Pad For Mobile Phone No.NPMP



Feature/Usage

- Printed sticky non-slip mat pad for mobile phone to avoid unexpected accident.

Breathable Non-woven Fabric Tape No.BNFT



Feature/Usage

- Air permeable non woven backing material, without release liner. Rain and wind resistant; permeable to water vapor. Further reduce moisture intrusion. Prevent moisture condensation.

Self Adhesive Stone Paper Tape No.SSPT



Feature/Usage

- Stone paper is waterproof.
- Recyclable.
- Photodegradable.
- Widely used.

Performance

Items	APCT	WIT	DSFT	NPMP	BNFT	SSPT
Backing	Aluminum Foam	PET	Fibreglass	Printed Embossed PE Film	Non-Woven Fabric	Stone Paper
Adhesive		Hot Melt		Acrylic Emulsion	Acrylic Emulsion Hot Melt	Hot Melt
Colors	Silver	Clear	White	Color	White	white, Solid Color Printed Design
Adhesion To Steel (N/in)	> 4.0	> 10	> 20	> 5.0	> 4.0	> 5.0
Tensile Strength (N/in)	> 50	> 100	> 200	> 40	> 12	> 30
Elongation (%)	> 20	N/A	> 5	> 350	> 20	200-300
Total Thickness (mm)	2.50±10%	0.100±10%	0.250±10%	0.200-0.350	0.200±10%	0.120±10%



Plate Mounting Tape No.PMT



Feature/Usage

- Specifically designed for mounting photopolymer plates in flexographic label printing. Highly compressible foam. Long lasting recovery characteristic. High bonding to plate to avoid edge lifting or plate movement.

Foam Wrap Roll No.FWR



Feature/Usage

- ECO-friendly protective foam wrap roll, impermeable to moisture, vibration, noise, strong thermal insulation and anti-collision, shock proof.

Nano Magic Tape No.NMT



Feature/Usage

- Paste photos or posters, fix carpet mats, organize and accept articles, anti-skid furniture, etc.
- The tape can be attached to the wall, the mobile phone or the flat panel can be attached to any surface.
- Seamless sticking, strong sticking force, double-sided removable, repetitive sticking, environmentally friendly and non-toxic.

Waterproof And Mildew-Fuddruckers No.WMPT



Feature/Usage

- Free cutting.
- Waterproof, grease-proof, and mildew-proof.
- No residue.
- Used for kitchen stove, dishwasher, gas station, toilet, floor gap, etc.
- It can be used normally after 12 hours.

Butyl Adhesive Tape No.BAT



Feature/Usage

- Strong adhesion to various material surfaces; excellent weather resistance, aging resistance and water resistance. For sunroom seal, window seal, roof crack and roof ridge seal color steel seal, pipe seal, etc.

Diecut Cloth Tape No.DCT



Feature/Usage

- It is widely used for packaging and binding. Special for sewing, splicing and thermal insulation materials

Performance

Items	PMT	FWR	NMT	WMPT	BAT	DCT
Backing	PE Foam /PET	EPE	PET Release Film	PET Film	Release Film	Cloth[50mesh] +PE Film
Adhesive	Acrylic	N/A	Acrylic		Butyl Rubber	Hot Melt
Colors	White		Clear		Black	Silver
Adhesion To Steel (N/in)	PET Side: ≥ 10 PE Foam Side: ≥ 15	N/A	≥ 29	≥ 15	Waterproof Materials ≥ 4 Cement Mortar ≥ 6	≥ 98
Tensile Strength (N/in)	≥ 120	≥ 10	≥ 20	≥ 180	N/A	≥ 200
Elongation (%)	≥ 120	N/A	≥ 300	≥ 120	N/A	N/A
Total Thickness (mm)	0.50±0.05	1.50±10%	2.00±0.05	0.80±0.05	1.00±10%	0.300±10%

